MAIZE LEVELLER

holaras 🗾

HYDRAULIC EXTENDING AND FOLDING ACTION 3 POINT, FRONT-END OR LOADER LINKAGE SHIFTS SILAGE UP TO 135 CM IN HEIGHT WORKING WIDTH OF UP TO 570 CM 300 CM TRANSPORT WIDTH

T +31 (0)543 466224
E info@holaras.nl
W www.holaras.nl

MAIZE LEVELLER



During the maize harvest, the distribution and compacting of silage can slow things down. Efficiency of the 'silage train' is constantly improving, meaning that hourly capacity is increasing dramatically.

The Holaras **maize leveller** is a must-have if you want to keep up with the pace. With the hydraulic **maize leveller**, the arriving maize can be distributed very quickly and efficiently. That means no more queuing silage trailers and tippers. Thanks to the leveller's individually extendable side wings, the edges of the silo can be filled to the top and neatly finished off. All leveller models can be fitted with lighting.

If your tractor or loader does not have enough hydraulic spool valves to fully operate the **maize leveller**, the implement can be fitted with an electro-hydraulic operating system for optimum use. This system can be combined with a universal Holaras remote control, allowing the central and wireless operation of all **maize leveller** functions.



The leveller can be attached to the tractor's 3 point linkage.



Both side panels fold in, giving the leveller a minimum transport width of 260 cm or 300 cm.



Can be front-end mounted or attached to a loader.

Technical specifications are purely indicative. We at all times reserve the right to make interim changes without prior notice.



TECHNICAL SPECIFICATIONS

	MES 570-H-115	MES 570-H-135	MES 470-H-115-F	MES 430-H-115-FK	MES 530-H-135-FK
Linkage	Three-point, cat II	Three-point, cat II	Front / Shovel	Front	Front
Working width (cm)	570	570	470	430	530
Load shift height (cm)	115	135	115	115	135
Transport width (cm)	300	300	300	260	260
Weight (kg)	1600	1750	1400	1350	1450
Additional weights	0	0	-	-	-
Loader attachment	-	-	0	0	0
Adjustability	Rear- and forward folding side wings			Forward folding side wings	
Hydraulic link	2 DW (or electro-hydraulic)				
Hydraulic capacity	App. 40 litres at 180 bar				

ACCESSORIES



STEGO silage compactor

- standard
- $^{\circ}$ optional
- n/a

www.holaras.nl

















Hoopman Machines B.V. Dinxperlosestraatweg 145 NL-7122 JP AALTEN

T +31 (0)543 466224 **E** info@holaras.nl **W** www.holaras.nl